

Revision Date 16.3.2016

Version 2.1

SECTION 1. Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Catalogue No. **Denature Ethanol 70%** ALCOH-AI70 Product name CAS-No. 64-17-5 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses Pharmaceutical production, Solvent, Food, Cosmetic raw material, Sterilize. 1.3 Details of the supplier of the safety data sheet Company APEX ALCO Co., Ltd. 630 Bangkhoontian-Shinetalay Rd., Thakarm, Bangkhoontian, Bangkok, Thailand. 1.4 Emergency telephone +66 2416 4677-8. number SECTION 2. Hazards identification 2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008) Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319 For the full text of the H-Statements mentioned in this Section, see Section 16. Classification (67/548/EEC or 1999/45/EC) F Highly flammable R11 For the full text of the R-phrases mentioned in this Section, see Section 16. 2.2 Label elements Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms Signal word Danger Hazard statements H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

www.apexalco.com

Apex Alco Co., Ltd.

632 Bangkhoontian-Shinetalay Rd., Thakarm, Bangkhoontian, Bangkok 10150, Thailand. Tel.+66 2416 4677-8 Fax.+66 2416 4679

ບຣີບັກ ເອເພົກຮ໌ ແອລໂກ້ ຈຳກັດ 632 ถนนบางขุนเทียน-ชายทะเล แของท่าข้าม เขตบางขนเทียน กรงเทพมหานคร 10150 Ins +66 2416 4677-8 Insans +66 2416 4679



Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

Precautionary statements

Prevention P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/bond container and receiving equipment. Response P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Storage P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)



Signal word Danger

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Index-No. 603-002-00-5

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula	C₂H₅OH	C₂H₅O (Hill)
Index-No.	603-002-00-5	
EC-No.	200-578-6	
Molar mass	46,07 g/mol	

Hazardous components (REGULATION (EC) No 1272/2008)

 Chemical Name (Concentration)

 CAS-No.
 Registration number ethanol (>= 50 % - <= 100 %)</td>

 Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

 64-17-5
 01-2119457610-43-XXXX

 Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

www.apexalco.com

Apex Alco Co., Ltd.

632 Bangkhoontian-Shinetalay Rd., Thakarm, Bangkhoontian, Bangkok 10150, Thailand. Tel.+66 2416 4677-8 Fax.+66 2416 4679 **บริษัท เอเพ็กซ์ แอลโก้ จำกัด** 632 ถนนบางขุนเทียน-ชายกะเล เของทำข้าม เขตบางขุนเทียน กรุงเทพมหานคร 10150 โทร.+66 2416 4677-8 โทรสาร.+66 2416 4679



Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Water, Foam, Carbon dioxide (CO2), Dry powder

Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at ambient temperatures. Pay attention to flashback. Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up





Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters





Catalogue No. Product name	Denature Ethanc ALCOH-AI70	bl 70%	
Derived No Effect Lev	el (DNEL)		
Worker DNEL, acute	Local effects	inhalation	1900 mg/m³
Worker DNEL, longterm	Systemic effects	dermal	343 mg/kg Body weight
Worker DNEL, longterm	Systemic effects	inhalation	950 mg/m³
Consumer DNEL, acute	Local effects	inhalation	950 mg/m³
Consumer DNEL, longterm	Systemic effects	dermal	206 mg/kg Body weight
Consumer DNEL, longterm	Systemic effects	inhalation	114 mg/m³
Consumer DNEL, longterm	Systemic effects	oral	87 mg/kg Body weight
Predicted No Effect Concentration (PNEC)			
PNEC Fresh water		0,96 mg/l	
PNEC Marine water		0,79 mg/l	
PNEC Fresh water sedimen	t	3,6 mg/kg	
PNEC Soil		0,63 mg/kg	
PNEC Aquatic intermittent re	elease	2,75 mg/l	
PNEC Sewage treatment pl	ant	580 mg/l	
PNEC oral		720 mg/kg	

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Safety glasses

Hand protection

full contact:

	Glove material: Glove thickness: Break through time:	butyl-rubber 0,7 mm > 480 min
splash contact:		
	Glove material:	Nitrile rubber
	Glove thickness:	0,40 mm
	Break through time:	> 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 730 Camatril® -Velours (splash contact).

www.apexalco.com



Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains. Risk of explosion.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties	
Form	liquid
Colour	colourless
Odour	alcohol-like
Odour Threshold	0,1 - 5058,5 ppm
рН	7,0 at 10 g/l 20 °C
Melting point	-117 °C
Boiling point/boiling range	78 °C at 1.013 hPa
Flash point	17 °C
Evaporation rate	No information available.
Flammability (solid, gas)	Not applicable
Lower explosion limit	3,5 %(V)
Upper explosion limit	15 %(V)
Vapour pressure	ca.59 hPa at 20 °C

www.apexalco.com

บริษัท เอเพ็กซ์ แอลโก้ จำกัด 632 ถนนบางชุนเทียน-ชายกะเล เของทำข้าม เขตบางชุนเทียน กรุงเทพมหานกร 10150 โทร.+66 2416 4677-8 โทรสาร.+66 2416 4679



Catalogue No. Product name	Denature Ethanol 70% ALCOH-AI70
Relative vapour density	No information available.
Density	0,873 - 0,886 g/cm3 at 20 °C
Relative density	No information available.
Water solubility	at 20 °C soluble
Partition coefficient: n- octanol/water	log Pow: -0,31 (experimental) (Lit.) Bioaccumulation is not expected.
Auto-ignition temperature	No information available.
Decomposition temperature	Distillable in an undecomposed state at normal pressure.
Viscosity, dynamic	1,2 mPa.s at 20 °C
Explosive properties	Not classified as explosive.
Oxidizing properties	none
9.2 Other data	
Ignition temperature	425 °C

SECTION 10. Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxi compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxide

silver, with, Nitric acid

silver compounds, with, Ammonia

potassium permanganate, with, conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum

Nitric acid, with, potassium permanganate

10.4 Conditions to avoid

Warming. www.apexalco.com



Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

10.5 **Incompatible materials** rubber, various plastics

10.6 Hazardous decomposition products no information available

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity LD50 Rat: 10.470 mg/kg OECD Test Guideline 401

Symptoms: Nausea, Vomiting

Acute inhalation toxicity LC50 Rat: 124,7 mg/l; 4 h ; vapour OECD Test Guideline 403

Symptoms: Possible damages:, mucosal irritations absorption

Acute dermal toxicity This information is not available. Skin irritation

Rabbit Result: No skin irritation OECD Test Guideline 404

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation Rabbit Result: Eye irritation OECD Test Guideline 405 Causes serious eye irritation.

Sensitisation Sensitisation test (Magnusson and Kligman): Result: negative

(IUCLID)

Germ cell mutagenicity Genotoxicity in vitro Ames test Salmonella typhimurium Result: negative Method: OECD Test Guideline 471 In vitro mammalian cell gene mutation test Mouse lymphoma test Result: negative Method: OECD Test Guideline 476

Carcinogenicity This information is not available.





Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

Reproductive toxicity This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure This information is not available.

Specific target organ toxicity - repeated exposure This information is not available. *Aspiration hazard*

This information is not available.

11.2 Further information

Systemic effects: euphoria After absorption of large quantities: Dizziness, inebriation, narcosis, respiratory paralysis Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish LC50 Leuciscus idus (Golden orfe): 8.140 mg/l; 48 h (IUCLID) *Toxicity to daphnia and other aquatic invertebrates* EC5 E.sulcatum: 65 mg/l; 72 h (Lit.) EC50 Daphnia magna (Water flea): 9.268 - 14.221 mg/l; 48 h (IUCLID) *Toxicity to algae* IC5 Scenedesmus quadricauda (Green algae): 5.000 mg/l; 7 d (Lit.)

Toxicity to bacteria

EC5 Pseudomonas putida: 6.500 mg/l; 16 h

(IUCLID)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) semi-static test NOEC Daphnia magna (Water flea): 9,6 mg/l; 9 d (ECHA)

12.2 Persistence and degradability

Biodegradability 94 % OECD Test Guideline 301E Readily biodegradable *Biochemical Oxygen Demand (BOD)* 930 - 1.670 mg/g (5 d)

(Lit.)

Theoretical oxygen demand (ThOD) 2.100 mg/g

(Lit.)





Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

Ratio COD/ThBOD
90 %
(Lit.)
12.3 Bioaccumulative potential
Partition coefficient: n-octanol/water
log Pow: -0,31
(experimental)
(Lit.) Bioaccumulation is not expected.
12.4 Mobility in soil
No information available.
12.5 Results of PBT and vPvB assessment
Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.
12.6 Other adverse effects
Additional ecological information
No interference with wastewater treatment plants are to be expected when used properly. Discharge into the environment must be avoided.
SECTION 13. Disposal considerations
Waste treatment methods
See www.retrologistik.com for processes regarding the return of chemicals and containers, or
contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)		
14.1 UN number	UN 1170	
14.2 Proper shipping name	ETHANOL	
14.3 Class	3	
14.4 Packing group	II	
14.5 Environmentally hazardous		
14.6 Special precautions for user	yes	
Tunnel restriction code	D/E	
Inland waterway transport (ADN) Not relevant		
Air transport (IATA)		
14.1 UN number	UN 1170	
14.2 Proper shipping name	ETHANOL	
14.3 Class	3	
14.4 Packing group	II	
14.5 Environmentally hazardous		
14.6 Special precautions for user	no	

Sea transport (IMDG)



	Denature Ethanol 70% ALCOH-AI70	
14.1 UN number	UN 1170	
14.2 Proper shipping name	ETHANOL	
14.3 Class	3	
14.4 Packing group	II	
14.5 Environmentally hazardo	us	
14.6 Special precautions for user	yes	
EmS	F-E S-D	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		

Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations	
Major Accident Hazard	SEVESO III
Legislation	FLAMMABLE LIQUIDS
	P5c
	Quantity 1: 5.000 t
	Quantity 2: 50.000 t
Occupational restrictions	Take note of Dir 94/33/EC on the protection of young people at work.
National legislation	
Storage class	3

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.		
H225	Highly flammable liquid and vapour.	
H319	Causes serious eye irritation.	
Full text of R-phrases referred to under sections 2 and 3		
R11	Highly flammable.	

Training advice

Provide adequate information, instruction and training for operators.

Labelling Hazard pictograms



Signal word Danger

www.apexalco.com

Apex Alco Co., Ltd.

632 Bangkhoontian-Shinetalay Rd., Thakarm, Bangkhoontian, Bangkok 10150, Thailand. Tel.+66 2416 4677-8 Fax.+66 2416 4679 **บธิษัท เอเพ็กซ์ แอลโก้ จำกัด** 632 ถนนบางขุนเทียน-ชายกะเล เของท่าข้าม เขตบางขุนเทียน กรุงเทพมหานกร 10150 โทร.+66 2416 4677-8 โทรสาร.+66 2416 4679





Catalogue No.	Denature Ethanol 70%
Product name	ALCOH-AI70

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Labelling (67/548/EEC or 1999/45/EC)

Symbol(s)	👲 F	Highly flammable
R-phrase(s)	11	Highly flammable.
S-phrase(s)	7-16	Keep container tightly closed. Keep away from sources of ignition - No smoking.
EC-No.	200-578-6	EC Label
Reduced lab	elling (≤125 ml)	
Symbol(s)	👲 F	Highly flammable

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

www.apexalco.com

Tel.+66 2416 4677-8 Fax.+66 2416 4679

