

Revision Date 16.8.2016

Version 2

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |
| CAS-No.       | 64-17-5              |

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pharmaceutical production, Solvent, Food, Cosmetic raw material In compliance with the conditions described in the annex to this safety data sheet.

#### 1.3 Details of the supplier of the safety data sheet

| Company                        | Bangkok Alcohol Industrial Co., Ltd  |
|--------------------------------|--|
|                                | 88/8 Moo7 Khaochang-Nongpong Rd,. Thungluang, Paktor,<br>Ratchaburi. Thailand. |
| 1.4 Emergency telephone number | +66 2416 4677-8.   |

#### **SECTION 2. Hazards identification**

2.1 Classification of the substance or mixture Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification (67/548/EEC or 1999/45/EC)

F Highly flammable

R11

For the full text of the R-phrases mentioned in this Section, see Section 16.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms



Signal word Danger

*Hazard statements* H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

Precautionary statements

Prevention P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/bond container and receiving equipment. Response P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Storage P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)



*Signal word* Danger

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Index-No. 603-002-00-5

#### 2.3 Other hazards

None known.

#### SECTION 3. Composition/information on ingredients

#### 3.1 Substance

| Formula    | C₂H₅OH       | C₂H₅O (Hill) |
|------------|--------------|--------------|
| Index-No.  | 603-002-00-5 |              |
| EC-No.     | 200-578-6    |              |
| Molar mass | 46,07 g/mol  |              |

#### Hazardous components (REGULATION (EC) No 1272/2008)

 

 Chemical Name (Concentration)

 CAS-No.
 Registration number ethanol (>= 50 % - <= 100 %)</td>

 Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

 64-17-5
 01-2119457610-43-XXXX

 Flammable liquid, Category 2, H225 Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 3.2 Mixture

Not applicable

www.bkkalcohol.com

Bangkok Alcohol Industrial Co., Ltd. (Factory) 88/8 Moo 7 Khaochang-Nongpong Rd., Thungluang, Paktor, Ratchaburi 70140, Thailand. Tel.+66 32 206 850-2 Fax.+66 32 206 853 **บริษัท กรุงเทพ อุดสาหกรรม แอลกอออล์ จำกัด** 88/8 หมู่ 7 ดนนเขาช้าง-หนองโป่ง ด่านตางหลอง อำเภอนากท่อ จังหวัดราชบุรี 70140 โทร.+66 32 206 850-2 โทรสาร.+66 32 206 853



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

#### **SECTION 4. First aid measures**

#### 4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed No information available.

#### **SECTION 5. Firefighting measures**

#### 5.1 Extinguishing media

*Suitable extinguishing media* Water, Foam, Carbon dioxide (CO2), Dry powder

*Unsuitable extinguishing media* For this substance/mixture no limitations of extinguishing agents are given.

#### 5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air and may spread along floors. Forms explosive mixtures with air at ambient temperatures. Pay attention to flashback. Development of hazardous combustion gases or vapours possible in the event of fire.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters In the event of fire, wear self-contained breathing apparatus.

#### Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

#### **SECTION 6. Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

## 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

## 6.3 Methods and materials for containment and cleaning up

www.bkkalcohol.com



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

#### 6.4 Reference to other sections

Indications about waste treatment see section 13.

#### SECTION 7. Handling and storage

#### 7.1 Precautions for safe handling

*Advice on safe handling* Observe label precautions.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

#### 7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

#### SECTION 8. Exposure controls/personal protection

### 8.1 Control parameters



| Catalogue No.<br>Product name            | Denature Ethanc<br>ALCOH-AI | ol 95%     |                       |
|--|-----------------------------|------------|-----------------------|
| Derived No Effect Leve                   | el (DNEL)                   |            |                       |
| Worker DNEL, acute                       | Local effects               | inhalation | 1900 mg/m³            |
| Worker DNEL, longterm                    | Systemic effects            | dermal     | 343 mg/kg Body weight |
| Worker DNEL, longterm                    | Systemic effects            | inhalation | 950 mg/m³             |
| Consumer DNEL, acute                     | Local effects               | inhalation | 950 mg/m³             |
| Consumer DNEL, longterm                  | Systemic effects            | dermal     | 206 mg/kg Body weight |
| Consumer DNEL, longterm                  | Systemic effects            | inhalation | 114 mg/m³             |
| Consumer DNEL, longterm                  | Systemic effects            | oral       | 87 mg/kg Body weight  |
| Predicted No Effect Concentration (PNEC) |                             |            |                       |
| PNEC Fresh water                         |                             | 0,96 mg/l  |                       |
| PNEC Marine water                        |                             | 0,79 mg/l  |                       |
| PNEC Fresh water sediment                |                             | 3,6 mg/kg  |                       |
| PNEC Soil                                |                             | 0,63 mg/kg |                       |
| PNEC Aquatic intermittent re             | lease                       | 2,75 mg/l  |                       |
| PNEC Sewage treatment pla                | ant                         | 580 mg/l   |                       |
| PNEC oral                                |                             | 720 mg/kg  |                       |
|  |                             |            |                       |

#### 8.2 Exposure controls

#### **Engineering measures**

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

#### Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Safety glasses

Hand protection

full contact:

|                 | Glove material:<br>Glove thickness:<br>Break through time: | butyl-rubber<br>0,7 mm<br>> 480 min |
|-----------------|--|-------------------------------------|
| splash contact: |  |                                     |
| ·               | Glove material:  | Nitrile rubber                      |
|                 | Glove thickness:   | 0,40 mm                             |
|                 | Break through time:  | > 120 min                           |

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 730 Camatril® -Velours (splash contact).



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Other protective equipment

Flame retardant antistatic protective clothing.

#### Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

#### Environmental exposure controls

Do not let product enter drains. Risk of explosion.

## SECTION 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties Form liquid Colour colourless Odour alcohol-like Odour Threshold 0,1 - 5058,5 ppm 7.0 pН at 10 g/l 20 °C Melting point -117 °C Boiling point/boiling range 78 °C at 1.013 hPa Flash point 17 °C No information available. Evaporation rate Flammability (solid, gas) Not applicable Lower explosion limit 3,5 %(V) Upper explosion limit 15 %(V) Vapour pressure ca.59 hPa at 20 °C



| Catalogue No.<br>Product name              | Denature Ethanol 95%<br>ALCOH-AI  |
|--|---|
| Relative vapour density                    | No information available.   |
| Density                                    | 0,805 - 0,812 g/cm3<br>at 20 °C   |
| Relative density                           | No information available.   |
| Water solubility                           | at 20 °C<br>soluble   |
| Partition coefficient: n-<br>octanol/water | log Pow: -0,31<br>(experimental)<br>(Lit.) Bioaccumulation is not expected. |
| Auto-ignition temperature                  | No information available.   |
| Decomposition temperature                  | Distillable in an undecomposed state at normal pressure.                    |
| Viscosity, dynamic                         | 1,2 mPa.s<br>at 20 °C   |
| Explosive properties                       | Not classified as explosive.  |
| Oxidizing properties                       | none  |
| 9.2 Other data                             |   |
| Ignition temperature                       | 425 °C  |

## SECTION 10. Stability and reactivity

## 10.1 Reactivity

Vapours may form explosive mixture with air.

## 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

## 10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxi compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxide

silver, with, Nitric acid

silver compounds, with, Ammonia

potassium permanganate, with, conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum

Nitric acid, with, potassium permanganate

## 10.4 Conditions to avoid Warming.



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

#### 10.5 **Incompatible materials** rubber, various plastics

10.6 Hazardous decomposition products no information available

#### SECTION 11. Toxicological information

#### 11.1 Information on toxicological effects

*Acute oral toxicity* LD50 Rat: 10.470 mg/kg OECD Test Guideline 401

Symptoms: Nausea, Vomiting

*Acute inhalation toxicity* LC50 Rat: 124,7 mg/l; 4 h ; vapour OECD Test Guideline 403

Symptoms: Possible damages:, mucosal irritations absorption

Acute dermal toxicity This information is not available. *Skin irritation* 

Rabbit Result: No skin irritation OECD Test Guideline 404

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

*Eye irritation* Rabbit Result: Eye irritation OECD Test Guideline 405 Causes serious eye irritation.

*Sensitisation* Sensitisation test (Magnusson and Kligman): Result: negative

#### (IUCLID)

Germ cell mutagenicity Genotoxicity in vitro Ames test Salmonella typhimurium Result: negative Method: OECD Test Guideline 471 In vitro mammalian cell gene mutation test Mouse lymphoma test Result: negative Method: OECD Test Guideline 476

*Carcinogenicity* This information is not available.



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |

*Reproductive toxicity* This information is not available.

Teratogenicity

This information is not available.

*Specific target organ toxicity - single exposure* This information is not available.

Specific target organ toxicity - repeated exposure This information is not available.

Aspiration hazard This information is not available.

## 11.2 Further information

Systemic effects: euphoria After absorption of large quantities: Dizziness, inebriation, narcosis, respiratory paralysis Handle in accordance with good industrial hygiene and safety practice.

## SECTION 12. Ecological information

## 12.1 Toxicity

Toxicity to fishLC50 Leuciscus idus (Golden orfe): 8.140 mg/l; 48 h(IUCLID)Toxicity to daphnia and other aquatic invertebratesEC5 E.sulcatum: 65 mg/l; 72 h(Lit.)EC50 Daphnia magna (Water flea): 9.268 - 14.221 mg/l; 48 h(IUCLID)Toxicity to algaeIC5 Scenedesmus quadricauda (Green algae): 5.000 mg/l; 7 d(Lit.)Toxicity to bacteriaEC5 Pseudomonas putida: 6.500 mg/l; 16 h

(IUCLID) *Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)* semi-static test NOEC Daphnia magna (Water flea): 9,6 mg/l; 9 d (ECHA)

## 12.2 Persistence and degradability

*Biodegradability* 94 % OECD Test Guideline 301E Readily biodegradable *Biochemical Oxygen Demand (BOD)* 930 - 1.670 mg/g (5 d)

(Lit.)

*Theoretical oxygen demand (ThOD)* 2.100 mg/g

(Lit.)



| Catalogue No. | Denature Ethanol 95% |
|---------------|----------------------|
| Product name  | ALCOH-AI             |
|               |                      |

| Ratio COD/ThBOD                    |  |
|------------------------------------|--|
| 90 %                               |  |
| (Lit.)                             |  |
| 12.3 Bioaccumulative potential     |  |
| Partition coefficient: n-octanol/w | vater  |
| log Pow: -0,31                     |  |
| (experimental)                     |  |
| (Lit.) Bioaccumulation is not exp  | pected.  |
| 12.4 Mobility in soil              |  |
| No information available.          |  |
| 12.5 Results of PBT and vPvB ass   | essment  |
|                                    | riteria for PBT or vPvB according to Regulation (EC) No    |
| 1907/2006, Annex XIII.             |  |
| 12.6 Other adverse effects         |  |
| Additional ecological informatio   |  |
|                                    | er treatment plants are to be expected when used properly. |
| Discharge into the environment     | must be avoided.   |
| SECTION 13. Disposal consideratio  | ns   |
| Waste treatment methods            |  |
| See www.retrologistik.com for p    | processes regarding the return of chemicals and containers |
| contact us there if you have fur   | her questions.   |
| SECTION 14. Transport information  |  |
| Land transport (ADR/RID)           |  |
| 14.1 UN number                     | UN 1170  |
| 14.9 Dreper chipping neme          | ETHANO   |

| 14.2 Proper shipping name                       | ETHANOL |
|---|---------|
| 14.3 Class                                      | 3       |
| 14.4 Packing group                              | II      |
| 14.5 Environmentally hazardous                  |         |
| 14.6 Special precautions for<br>user            | yes     |
| Tunnel restriction code                         | D/E     |
| Inland waterway transport (ADN)<br>Not relevant |         |
| Air transport (IATA)                            |         |
| 14.1 UN number                                  | UN 1170 |
| 14.2 Proper shipping name                       | ETHANOL |
| 14.3 Class                                      | 3       |
| 14.4 Packing group                              | II      |
| 14.5 Environmentally hazardous                  |         |
| 14.6 Special precautions for<br>user            | no      |

## Sea transport (IMDG)



or

| 5   | Denature Ethanol 95%<br>ALCOH-AI |
|---|----------------------------------|
| 14.1 UN number  | UN 1170                          |
| 14.2 Proper shipping name   | ETHANOL                          |
| 14.3 Class  | 3                                |
| 14.4 Packing group  | II                               |
| 14.5 Environmentally hazardou   | us                               |
| 14.6 Special precautions for<br>user  | yes                              |
| EmS   | F-E S-D                          |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code |                                  |

Not relevant

## **SECTION 15. Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| EU regulations            |  |
|---------------------------|--|
| Major Accident Hazard     | SEVESO III   |
| Legislation               | FLAMMABLE LIQUIDS  |
| -                         | P5c  |
|                           | Quantity 1: 5.000 t  |
|                           | Quantity 2: 50.000 t   |
| Occupational restrictions | Take note of Dir 94/33/EC on the protection of young people at work. |
| National legislation      |  |
| Storage class             | 3  |
|                           |  |

#### 15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out.

## **SECTION 16. Other information**

| Full text of H-Statements referred to under sections 2 and 3. |                                     |  |
|---|-------------------------------------|--|
| H225  | Highly flammable liquid and vapour. |  |
| H319  | Causes serious eye irritation.      |  |
| Full text of R-phrases referred to under sections 2 and 3     |                                     |  |
| R11   | Highly flammable.                   |  |

#### **Training advice**

Provide adequate information, instruction and training for operators.

Labelling Hazard pictograms



*Signal word* Danger



| Catalogue No. | Denature Ethanol 95% |  |
|---------------|----------------------|--|
| Product name  | ALCOH-AI             |  |

#### Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

#### Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

#### Labelling (67/548/EEC or 1999/45/EC)

| Symbol(s)   | 👲 F              | Highly flammable  |
|-------------|------------------|---|
| R-phrase(s) | 11               | Highly flammable.   |
| S-phrase(s) | 7-16             | Keep container tightly closed. Keep away from sources of ignition - No smoking. |
| EC-No.      | 200-578-6        | EC Label  |
| Reduced lab | elling (≤125 ml) |   |
| Symbol(s)   | 👲 F              | Highly flammable  |

## Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

#### Distributor

-APEX ALCO Co.,Ltd.

632 Bangkhoontian-Shinetalay Rd., Thakarm,Bangkhoontian,Bangkok 10150, Thailand. Phone:+(662)-416-4677-8 Fax:+(662)-416-4679

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

